



**FITTING INSTRUCTIONS FOR RGH0006BK REAR HUGGER FOR
HONDA CBR 1000 RR (FIREBLADE) 2008-**



**THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW.
DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.**

**Please note that the way the kit is packed does not necessarily represent the way of
mounting to the bike**

Kit Contents:

- 1 x HONDA HUGGER HUG0006 (WITH VELCRO ADHESIVE PADS IN POSITION).
- 3 x M5x25mm LONG BUTTON HEAD BOLTS.
- 1 x R&G LARGE BUBBLE STICKER.

TOOLS REQUIRED

- 3mm A/F METRIC ALLEN KEY.
- 5mm A/F METRIC ALLEN KEY.



PICTURE 1



PICTURE 2



PICTURE 3



PICTURE 4



PICTURE 5



PICTURE 6



FITTING INSTRUCTIONS

- REMOVE THE BOLT ARROWED IN PICTURE 1.
- REMOVE THE BOLT ARROWED IN PICTURE 2.
- REMOVE THE BOLT ARROWED IN PICTURE 3.
- OFFER THE R&G HUGGER INTO POSITION AND ALIGN WITH THE HOLES.
- PLACE TWO OF THE NEW BOLTS FROM KIT THROUGH THE ORIGINAL BRAKE LINE CLAMPING BRACKETS AND INTO THE SWING-ARM ON THE RIGHT HAND SIDE AS SHOWN IN PICTURES 4 AND 5 (ONLY ENGAGE BY 5mm AT THIS STAGE).
- FIT THE REMAINING BOLT AS SHOWN IN PICTURE 6 (ONLY ENGAGE BY 5mm AT THIS STAGE).
- GENTLY LIFT THE LEFT HAND SIDE OF THE HUGGER AND REMOVE THE BACKING OF BOTH VELCRO STRIPS AND PRESS THE HUGGER FIRMLY INTO POSITION.
- TIGHTEN ALL THREE BOLTS ENSURING THE HUGGER IS CENTRAL AND CLEAR OF THE WHEEL (ALSO ENSURE THE ANTI ROTATION TAGS FIT INTO THE HOLES IN THE HUGGER).



INSTRUCTIONS DE MONTAGE
RGH0006BK Garde boue
HONDA CBR 1000 RR (FIREBLADE) 2008-



VERIFIER QUE TOUTES LES PIECES MONTREES SUR LES PHOTOS SONT BIEN PRESENTES DANS LE KIT.

La façon dont le kit est emballé ne représente pas nécessairement la façon de le monter sur la moto.

Le kit doit contenir:

- 1 x Garde boue HUG0006 (avec le Velcro en position).
- 3 x M5x25mm Longs boulons à tête ronde.
- 1 x R&G Grand sticker en gomme.

Outils requis

- 3mm A/F Clef Allen.
- 5mm A/F Clef Allen.



Photo 1



Photo 2



Photo 3



Photo 4



Photo 5



Photo 6



Instructions de montage:

- Enlever le boulon (photo 1).
- Enlever le boulon (photo 2).
- Enlever le boulon (photo 3).
- Mettre le garde boue en position et l'aligner avec les trous.
- Placer 2 des nouveaux boulons du kit à travers les supports de ligne de frein et dans le bras oscillant du coté droit (photo 4 et 5). N'engager qu'à 5mm à ce stade.
- Installer le boulon restant (photo 6). N'engager qu'à 5mm à ce stade.
- Lever doucement le coté gauche du garde boue et Enlever le support des 2 bandes de Velcro puis mettre correctement le garde boue en position.
- Serrer les 3 boulons en s'assurant que le garde boue soit bien centré et dégagé de la roue arrière. (S'assurer que les balises anti rotations soient bien positionnées).

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.