




FITTING INSTRUCTIONS FOR CP0286 CRASH PROTECTORS
DUCATI DIAVEL 2011



PICTURE 'A'



PICTURE 'B'



REAR OF BIKE

FRONT OF BIKE

PICTURE 'C'


THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW.
DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*



THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)



LEGEND

- ITEM 1= M12 ENGINE-BAR (300mm LONG) (EB059) (x1).
- ITEM 2= RIGHT HAND SIDE EXTENSION (95mm LONG) (E0050) (x1).
- ITEM 3= PROTECTOR (B0061 WITH CS340 12mm) (x2).
- ITEM 4= PROTECTOR CAPS (BC0002) (x2).
- ITEM 5= M12 PLAIN WASHERS (x2).
- ITEM 6= LOCK-WASHERS (LW0001) (x2).
- ITEM 7= M12x1.25x60mm LONG HEX HEAD BOLTS (x2).
- ITEM 8= RIGHT HAND SIDE SPACER (32.5mm LONG) (S0442) (x1).
- ITEM 9= LEFT HAND SIDE EXTENSION (67.5mm LONG) (E0049) (x1).
- ITEM 10= LEFT HAND SIDE SPACER (35mm LONG) (S04421) (x1).

TOOLS REQUIRED

- Socket set to include 14, 15, 19 and 22mm sockets and wrench.
 - Torque wrench (up to 40Nm).



INSTRUCTIONS

- Undo the nut on the engine bolt located mid engine (as arrowed in pictures A and B).
- Take R&G engine bar (ITEM 1) and, with a soft hammer, use it to knock through the OEM bolt leaving equal amounts protruding on each side of the frame.
- Fit the shorter extension (ITEM 9) on the left hand side of the engine bar (the smaller diameter goes inside the frame), please ensure at least 15mm of thread is engaged.
- Fit the longer extension (ITEM 2) on the right hand side of the engine bar (the smaller diameter goes inside the frame), please ensure at least 15mm of thread is engaged and tighten. Do not exceed 40nm of torque.
- Place the longer tube spacer (ITEM 10) over extension (ITEM 9) on left hand side (this is cosmetic only).
- Place the shorter tube spacer (ITEM 8) over extension (ITEM 2) on right hand side (this is cosmetic only).
- Take the M12 bolts (ITEMS 7) and slide a plain washer (ITEMS 5) up to the head of the bolt, followed by one of the shake proof washers (ITEMS 6). Pass the bolts with washers through the protectors (ITEM 3) so the bolt head goes into counter-bore.
- Fit the protectors with spacers to either side of the bike. **PLEASE NOTE BOBBIN MUST BE POSITIONED AS IN PICTURE 'C' ABOVE WITH BIGGER END TOWARD FRONT OF BIKE.** Tighten bolt until you feel some compression from inside the protector. Turn a little more so that you feel the compression increase slightly. Then apply a quarter turn. Do not over tighten as damage can occur to the bike. Do not exceed 40nm of torque.
- When the protectors are tight fit the protector caps (ITEM 4) in to the protector.
- If not already fitted fit bubble sticker into recess of bobbin cap.

DUE TO THE RISK OF CROSS-THREADING OF BOLTS ETC; WE ALWAYS RECOMMEND THAT OUR PRODUCTS BE FITTED BY ONE OF OUR OFFICIAL DEALERS OR A QUALIFIED MECHANIC.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



INSTRUCTIONS DE MONTAGE POUR CP0286 SUPPORT DE PLAQUE
D'IMMATRICULATION

DUCATI DIAVEL 2011




Image 'A'



Image 'B'



Arriere de la moto

devant de la moto

Image 'C'


Verifier le contenu de la boite avant de deballer les pieces

**LA FACON DONT LE KIT EST EMBALLE NE REPRESENTE PAS NECESSAIREMENT LA FACON DE
LE MONTER SUR LA MOTO**

Notez que dans les cas où les kits sont emballés avec des rondelles en caoutchouc,
composantes du boulon - les rondelles en caoutchouc doivent être jetées !



LES PARTIES EXPOSEES NE SONT QUE REPRESENTATIVES



LEGENDE

- Article 1= M12 PROTECTION MOTEUR (300mm LONG) (EB059) (x1).
- Article 2= EXTANSION COTE DROIT (95mm LONG) (E0050) (x1).
- Article 3= PROTECTION (B0061 WITH CS340 12mm) (x2).
- Article 4= CAPUCHONS DE PROTECTION (BC0002) (x2).
- Article 5= M12 RONDELLES PLATES (x2).
- Article 6= RONDELLES DE BLOCAGE (LW0001) (x2).
- Article 7= M12x1.25x60mm LONG BOULON A TETE HEXAGONALE (x2).
- Article 8= ENTRETOISE COTE DROIT (32.5mm LONG) (S0442) (x1).
- Article 9= EXTANSION COTE DROIT (67.5mm LONG) (E0049) (x1).
- Article 10= ENTRETOISE COTE GAUCHE (35mm LONG) (S04421) (x1).

OUTILS REQUIS

- Jeu de douilles et cles de 14, 15, 19 et 22mm
- Clé dynamométrique (jusqu'à 40Nm).

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



INSTRUCTIONS

- Desserrez l'écrou sur le boulon situe a mi-moteur (comme indiquée avec A et B).
- Prendre la protection R&G (article 1) et, avec un maillet, frapper à travers le boulon OEM laissant des quantités égales de chaque côté du cadre.
- Mettre en place l'extension plus courte (article 9) sur le côté gauche du moteur (le plus petit diamètre va à l'intérieur du cadre), assurer un degagement minimum de 15 mm.
- Mettre en place le plus d'extension (article du cote droit du moteur , le plus petit diamètre va à l'intérieur du cadre), assurer un degagement minimum de 15 mm et serrer. Ne pas dépasser 40 nm de couple.
- Placer l'entretoise plus longue, (article 10) sur l'extension (article 9) sur le côté gauche.
- Placer l'entretoise plus courte (article 8) sur l'extension (article 2) sur le côté droit.
- Prendre les boulons M12 (article 7) et faites glisser une rondelle plate (points 5) à la tête du boulon, et ensuite l'une des rondelles « SHAKE PROOF » (article 6). Pass les boulons avec les rondelles par la protection (point 3) de sorte que la tête du boulon passe en contre-alésage.
- Mettre en place les protections avec des entretoises de chaque côté de la moto. S'IL VOUS NOTEZ QUE LA BOBINE DOIT ETRE INSTALLEE COMME DANS « C » vers le devant de la moto. Serrer la vis jusqu'à ce que vous sentiez une certaine compression de l'intérieur du protecteur. Compresser legerement. Ne serrez pas trop car les dommages peuvent se produire à la moto. Ne pas dépasser 40 nm de couple.
- Une fois que tout est bien installé, pose le cache R&G Racing pour plus d'esthetisme

En raison du risque de contre-filetage de boulons, etc, nous recommandons toujours que nos produits soient mis en place par l'un de nos revendeurs officiels ou un mécanicien qualifié.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com