

Fitting Instructions for DG0025 BK Downpipe Grille SUZUKI GSX-S 750 2017-



In This Kit There Should Be 1 x Downpipe Grille (DG0025). 1 x M6 x 30mm Button Head Bolts. 2 x M6 Washers.


Digital copies of these instructions are available to download from www.rg-racing.com

GENERAL TORQUE SETTINGS

M4 BOLT = 8Nm M5 BOLT = 12Nm M6 BOLT = 15Nm M8 BOLT = 20Nm M10 BOLT = 40Nm







Picture 1

Picture 2

TOOLS REQUIRED

- Socket set to include 10mm socket & wrench.
 - 4mm A/F allen key

FITTING INSTRUCTIONS

- Remove the lower radiator mounting bolt as arrowed in Picture 1 using a 10mm socket and a wrench.
- If fitting R&G Downpipe Grille without R&G Radiator Guard, take the M6 bolt (Item 1) and the two M6 Washers (Item 2A & 2B) and locate them to the top mount of the downpipe grille as shown in Picture 2.
- If fitting R&G Downpipe Grille with R&G Radiator Guard, take the M6 bolt (Item 1) and one M6 washer (Item 2A) and locate them to the top mount of the downpipe grille with the washer sits against the bolt's head.
- Offer the downpipe grille assembly in front of the exhaust pipes, locate the top mount to the lower mounting point of the OEM radiator guard and loosely fit the bolt to the mount.
- Gently clip in the two downpipe grille's exhaust clips to the nearest two exhaust pipes.
- Tighten the M6 bolt on the top mount to a specified torque setting.

ISSUE 1 03/07/2017 (HH)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ



Notice de montage DG0025 BK Grille de collecteur d'échappement SUZUKI GSX-S 750 2017-



Le kit doit contenir: 1 x Grille de collecteurs d'échappement (DG0025). 1 x M6 x 30mm Boulons 2 x M6 Rondelles

Notice disponible au téléchargement sur www.rg-racing.com

VALEURS DE SERRAGE RECOMMANDEES

M4 BOULON = 8Nm


M5 BOULON = 12Nm


M6 BOULON = 15Nm

M8 BOULON = 20Nm

M10 BOULON = 40Nm







Picture 1

Picture 2

OUTILS REQUIS

- Clé à cliquet + douille 10mm.
 - Clé Allen 4mm.

NOTICE DE MONTAGE

- Enlever le boulon de fixation du radiateur inférieur, voir photo 1 en utilisant une clé à cliquet + douille de 10mm.
- Si vous Montez la grille de collecteurs d'échappement R&G sans la grille de protection radiateur R&G, prendre le boulon M6 (article 1) et les 2 rondelles M6 (article 2A & 2B) et placez-les sur le support supérieur de la grille de collecteurs d'échappement, voir photo 2
- Si vous montez la grille de collecteurs d'échappement R&G avec la grille de protection radiateur R&G, prendre le boulon M6 (article 1) et une rondelle M6 (article 2A) et placez-les sur le support supérieur de la grille de collecteurs d'échappement avec la rondelle contre la tête du boulon.
- Monter l'ensemble à l'avant des tuyaux d'échappement, placez le support supérieur sur le point de fixation inférieur de la grille de protection radiateur d'origine puis insérez le boulon sur le support.
- Cliper délicatement les 2 clips de grille de collecteurs d'échappement au plus proche des tuyaux d'échappement.
- Serrer le boulon M6 sur le support supérieur à la valeur de serrage recommandée.

ISSUE 1 03/07/2017 (HH)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

R&G Racing



Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

${\bf R\&G~RACING~RETURNS~POLICY~(NON\text{-}FAULTY~GOODS)}$

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.