



FITTING INSTRUCTIONS FOR EH0046BK/ EXHAUST HANGER
SUZUKI GSXR 600/750 2008-



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

- Remove OEM rear foot pegs/exhaust hanger.
- Place the two shorter M8 button head bolts from kit through the two top holes in the R&G hanger.
- Offer up to bike as shown above and engage threads (do not tighten yet).
- Place the 8mm washer onto longer M8 button head bolt from kit and position as arrow through exhaust mount as shown.
- Place 8mm washer and M8 nyloc nut onto exposed end of bolt and tighten all bolts evenly.
- Please ensure when the motorcycle is being used that no parts are in such a position that they may collide/damage other bike parts (this is particularly important if using after-market cans or exhaust systems).

Please note that it is your responsibility to ensure that no part of the exhaust hanger or exhaust assembly fouls or comes into contact with other parts of the machine. Do not ride the motorcycle until this aspect has been verified and you have compressed the rear suspension (if appropriate to the design of the motorcycle) to test this thoroughly.



Instructions de montage
EH0046BK/ Support pot d'échappement
SUZUKI GSXR 600/750 2008



LA FACON DONT LE KIT EST EMBALLE NE REPRESENTE PAS NECESSAIREMENT LA FACON DE LE MONTER SUR LA
MOTO

Notez que dans les cas où les kits sont emballés avec des rondelles en caoutchouc, composantes du boulon - les rondelles en caoutchouc doivent être jetées !

- Retirez les repose-pieds arrière / support pot d'échappement d'origine
- Placer les deux boulons courts M8 à travers les deux trous sur le dessus du support R&G.
- Installer le support sur la moto comme le montre la photo ci dessus. (Ne pas serrer pour le moment).
- Placer la rondelle de 8mm sur le long boulon à tête ronde M8 du kit et positionnez-le comme indiqué, à travers le support.
- Placer la rondelle de 8mm et l'écrou M8 en nyloc sur l'extrémité oppose du boulon puis serrer tous les boulons de façon égale.
- Assurez-vous que lorsque vous utiliserez la moto, aucune partie ne pourra rentrer en collision/contact avec une autre, pouvant entraîner des dommages sur la moto.

Il est de votre responsabilité de veiller à ce qu'aucune partie de l'ensemble d'échappement puisse rentrer en contact avec une autre partie de la machine. Ne pas



conduire la moto jusqu'a ce que cet aspect ait ete verifie et après avoir compresse la suspension arriere.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.