

FITTING INSTRUCTIONS FOR LP0074BK LICENCE PLATE BRACKET HONDA CB1000R 2008-



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away*!

PLEASE READ ALL INSTRUCTIONS BEFORE COMMENCING

NOTE YOU WILL NEED TO GLUE THE LIGHT SHROUD TO THE LED LICENCE PLATE LIGHT BEFORE FITTING USING SUPER GLUE.

YOU WILL NEED THE FOLLOWING TOOLS TO COMPLETE THIS JOB

Socket set to include 6mm, 8mm and 10mm sockets and wrench.

Set of metric allen keys.

Phillips screwdriver.


10mm spanner.

Electrical stripping and crimping pliers.

- Remove pillion seat (using key).
- Remove cable cover shown in picture A.




PICTURE A




PICTURE B



- Remove OEM licence plate bracket under tray, (you will have to remove six Phillips type screws from underneath as arrowed in picture B and unclip it).
- Disconnect wiring plugs to rear light, No plate light and indicators.
- Feed all wires through under tray into under seat compartment.
- Remove OEM licence plate bracket you will need to remove 4 bolts from under seat compartment as arrowed below.



- If using OEM indicators remove them from OEM licence plate bracket (blue = right-hand orange = left-hand).
- Fit new licence plate light to new licence plate bracket. To connect new licence plate light (new red ---OEM black/grey and new black---OEM green) please use heat shrink to protect wires at light end of cable.
- Fit indicators of your choice (if fitting mini's R&G product code RG370) to cable cover/indicator bracket, (if using OEM indicators we suggest reducing length of threaded stud) shown below left.
- Fit new licence plate bracket to the two furthest back original mounting holes using two of the four spacers provided (to fit between licence plate bracket and mounting face with smaller spigot going into holes in under tray) using two M6x20mm long button head bolts and M6 nyloc nuts, do not tighten yet.







PICTURE C (note shape of cover has changed)

• Place the two remaining M6x25mm long button head bolts through the remaining mounting holes from top and positioning the two remaining spacers between licence plate bracket and mounting face with smaller spigot going into holes in under tray, do not use nyloc nuts at this stage.

R&G Racing



- Tighten the two furthest back nuts and bolts.
- Offer new cable cover/indicator bracket into position while feeding indicator and licence plate light wires through holes provided. Ensure that the forward holes go over the two front mounting bolts and fix to the main bracket using the three M6x 6mm long button bolts as shown in picture above left and picture C.
- Carefully remove the forward bolts and feed from underneath through cable cover/indicator bracket, licence plate bracket and spacers already positioned, use nyloc nuts and tighten.
- Fit remaining nyloc nut to the bolt first fitted to licence plate bracket and tighten.
- Reroute rear light wires into under seat compartment and connect all wiring plugs as shown below.



- Suggest checking all lights at this stage.
- Refit cable cover.
- Refit pillion seat.
- Refit licence plate.
- IMPORTANT: IF FITTING A FULL-SIZE LICENCE PLATE AND PLACING IT FAR DOWN ON THE LICENCE PLATE HANGER, THERE IS A SMALL CHANCE OF THE LICENCE PLATE HITTING THE BACK WHEEL UNDER HEAVY LOAD AND OVER LARGE BUMPS IN THE ROAD. IT IS YOUR RESPONSIBILITY TO CHECK FOR THIS POSSIBILITY AND TAKE AVOIDING ACTION. FAILURE TO CHECK THIS COULD RESULT IN SERIOUS INJURY.
- Depending on local laws, attach enclosed red reflective tape in an appropriate location.
- Please test the indicators, rear/brake light and licence plate illuminator before riding.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be



liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.