



Fitting Instructions for DG0003 BK Downpipe Grille
KAWASAKI ZX10R 2011



- Remove or loosen the side fairing to allow access to the lower radiator-mounting bolt.
- Undo and remove lower radiator mounting bolt.
- Fit the downpipe grille into position as shown above and secure to the lower radiator mount using original bolt (ensure the lower hole in the downpipe grille is aligned with the push rivet hole arrowed above).
- Refit side fairing.
- Refit the push rivet ensure the lower hole in the downpipe grille is engaged.

ISSUE 1 25/02/2011 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing
Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



FRANCE
Instructions de montage de la grille DG0003 BK
KAWASAKI ZX10R 2011



- Enlevez ou desserrez le carénage latéral pour avoir accès à la vis de fixation inférieure du radiateur.
- Enlevez la vis de fixation inférieure du radiateur.
- positionnez la grille comme indiqué sur la photo et bloquez la grille en utilisant la vis de fixation inférieure du radiateur. (précédemment enlevée) (assurez-vous que la grille soit alignée avec le trou du rivet poussoir montré en photo en bas).
- Remontez le carénage.
- Remplacez les vis de carénage et le rivet poussoir.



Montageanleitung für das Krümmerschutzgitter DG0003 BK
KAWASAKI ZX10R 2011



- Entfernen oder lösen Sie die Seitenverkleidung, um Zugang zur Montageschraube für den unteren Kühler zu ermöglichen.
- Lösen und entfernen Sie die untere Montageschraube für den unteren Kühler.
- Montieren Sie das Krümmerschutzgitter in Position, wie oben abgebildet, und befestigen Sie den unteren Montagehalter für den Kühler mit der Originalschraube (bitte darauf achten, dass das untere Loch im Krümmerschutzgitter und das markierte Loch (oben im Bild) für die Linsenkopfschraube übereinander sind).
- Montieren Sie die Seitenverkleidung wieder.
- Montieren Sie die Linsenkopfschraube und überprüfen Sie, dass das untere Loch im Kühlerschutzgitter eingerastet ist.