

FITTING INSTRUCTIONS FOR FP0042BK FORK PROTECTORS YAMAHA R6 '99-'02



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

- INSERT SPACER INTO THE LHS OF THE FRONT SPINDLE
- PUT THE SPINDLE BAR THROUGH THE FRONT SPINDLE AND PLACE THE BOBBINS OVER EITHER END. THE BOBBIN WITH NO NECK GOES ON THE LHS.
- FIT WASHERS AND NUTS AND TIGHTEN
- PLACE NYLOC NUTS ON EACH END OF THE BAR AND TIGHTEN THEM – DO NOT OVERTIGHTEN ! JUST TIGHTEN THEM UNTIL THEY LOCK UP – AS THEY ARE NYLOC NUTS THEY WILL HOLD TIGHT.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes.

Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products.

On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned.

These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected)

Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor.

Goods must be in re-sellable condition, in the opinion of R&G Racing.

All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase).

The customer must pay any and all carriage charges.

No returns of discontinued products, unless within 14 days of purchase.

This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



Notice de montage

FP0042BK PROTECTION DE FOURCHE YAMAHA R6 99-02



Conseil de montage:

1- Mettre la pièce en aluminium sur le côté gauche de l'axe avant de la moto.

2- Glisser l'axe livré dans le kit R&G à travers l'axe d'origine. Puis placer les deux protections sur les extrémites, le tampon ayant une collerette devra être positionné sur le côté gauche.

3- Mettre une rondelle de chaque côté de l'axe R&G.

4- Mettre un écrou autobloquant sur chaque extrémité. Ne pas serrer trop fermement car l'écrou nillstop bloquera l'assemblage.