


FITTING INSTRUCTIONS FOR ECC0122 RHS ENGINE CASE COVER KAWASAKI VERSYS 2010 AND ER-6 F&N 2009 MODELS



PICTURE A

In this kit there should be:

1 x Engine Case Cover (ECC0122) 4 x M6x35mm long button head bolts

PLEASE READ THESE INSTRUCTIONS FULLY BEFORE STARTING

- Please make sure the engine is cold before proceeding with the fitting of the R&G cover.
- On the ER-6 F model you will have to remove the lower fairing from bike to allow fitment of the engine case cover.
- Remove the four engine case bolts arrowed above. Hold the cover loosely over the case to help identify the correct ones. DO NOT REMOVE ALL OF THE CASE BOLTS.
- Offer up the R&G cover to the engine and carefully fit it over the engine casing. Ensure that the four R&G bolt holes are lined up with the holes in the engine casing, and then push on as far as it will go.
- With a 4mm Allen key tighten the bolts equally so that they pull the cover into place. DO NOT FULLY TIGHTEN.
- Finally use a torque wrench set at 10 nm (7 Lb ft) to fully tighten.
- On the ER-6 F model refit fairing.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.

R&G RACING

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 <u>www.rg-racing.com</u> Email: <u>info@rg-racing.com</u>



- NOTE for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent
- AVOID HARMFUL CHEMICALS IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.
- R&G will accept no liability if the above procedure and torque settings are not followed.

ISSUE 1 24/01/2012 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



FITTING INSTRUCTIONS

ECC0122 RHS ENGINE CASE COVER KAWASAKI VERSYS 2010 AND ER-6 F&N 2009 MODELS




Photo A

Ce kit contient:

1 x protection carter moteur (ECC0122) 4 x M6x35mm longs boulons à tête ronde

Lire attentivement la notice avant de procéder au montage

- Assurez-vous que le moteur soit froid avant de procéder au montage.
- Sur le modèle ER-6 F, vous devrez enlever la partie basse du carénage de la moto pour installer la protection.
- Enlever les 4 boulons du carter moteur comme sur la photo du dessus.
- Tenir la protection autour du carter pour aider à identifier les bons trous.

R&G RACING

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



- Ne pas enlever tous les boulons du carter moteur.
- Mettre en place la protection R&G au moteur en prenant soin de bien le positionner autour du carter moteur.
- S'assurer que les trous de la protection R&G soient bien alignés avec ceux du carter, puis pousser jusqu'à la limite.
- Avec une clé Allen de 4mm, serer les boulons de façon égale pour qu'ils mettent automatiquement la protection en place.
- NE PAS SERRER COMPLETEMENT
- Pour finir, utilise une clé dynamométrique réglée à 10nm (7 Lb ft) pour serrer définitivement.
- Sur le modèle ER-6 F, remettre le carénage du bas.
- L'équipe R&G Racing vous suggère de vérifier le serrage régulièrement, lorsque la moto est propre, au moins une fois par mois.
- NOTE: Pour nettoyer la protection, utilisez uniquement un chiffon doux et un agent nettoyant peu fort
- NE PAS UTILISER D'AGENT CHIMIQUE QUI POURRAIT ALTERER L'EFFICACITE DE LA PROTECTION.
- R&G n'acceptera pas d'être tenu responsable en cas d'utilisation d'un agent chimique qui aurait détérioré la protection ou en cas de mauvais serrage de couple.

ISSUE 1 24/01/2012 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.