

FITTING INSTRUCTIONS FOR SP0074BK SWINGARM-PROTECTORS YAMAHA WR450F 2012-2015


SP0074



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW. DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike.

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)



LEGEND

ITEM 1 = SPINDLE BAR (SB120=325mm LONG) (x1) ITEM 2 = RIGHT-HAND SPACER (S0993) (x1). ITEM 3 = LEFT-HAND SPACER (S0330) (x1). ITEM 4 = CRASH PROTECTOR (B0461) (x2). ITEM 5 = M8 WASHERS (19mm OD) (x2). ITEM 6 = M8 NYLOC NUTS (x2)

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away*!

TOOLS REQUIRED

• 2 x 13mm A/F SOCKETS AND WRENCHES.

Torque wrench

R&G Racing Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



FITTING INSTRUCTIONS

- Place the spindle bar (item 1) through the rear wheel spindle from the right hand side.
- Place the RHS spacer (item 2) into the rear wheel spindle on the right hand side. Follow by a crash protector (item 4), M8 washer (item 5) and M8 nyloc nut (item 6). Do not fully tighten the nut at this stage.
- Place the LHS spacer (item 3) into the rear wheel spindle on the left hand side. Follow by a crash protector (item 4), M8 washer (item 5) and M8 nyloc nut (item 6).
- Using a 13mm socket and a wrench on each side, tighten both nyloc nuts at the same time, ensure that the nyloc nuts are fully engaged with the thread on the spindle bar. Tighten to 20Nm. DO NOT OVER-TIGHTEN—THE NYLOC NUTS WILL HOLD IT TIGHT.

ISSUE 1 10/10/2016 (HH)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P - at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



SP0074


NOTICE DE MONTAGE POUR SP0074BK PROTECTION BRAS OSCILLANT YAMAHA WR450F 2012-2015



Le kit contient les articles exposés ci-dessous, vérifier que toutes les pièces soient présentes avant de procéder au montage.

LA FAÇON DONT LE KIT EST EMBALLE NE CORRESPOND PAS FORCEMENT A LA FAÇON DE MONTER LES PIECES SUR LA MOTO.

<u>LES PARTIES PRESENTEES PEUVENT ETRE UNIQUEMENT</u> REPRESENTATIVES (POUR LA CLARTE DES INSTRUCTIONS UNIQUEMENT)



LEGENDE

ARTICLE 1 = BARRE D'AXE (SB120=325mm LONG) (x1)ARTICLE 2 = ENTRETOISE COTE DROIT (S0993) (x1).ARTICLE 3 = ENTRETOISE COTE GAUCHE (S0330) (x1).ARTICLE 4 = PROTECTION CRASH (B0461) (x2).ARTICLE 5 = M8 RONDELLES (19mm OD) (x2).ARTICLE 6 = M8 ECROUS (x2)

Notez que si les kits sont emballés avec des rondelles en caoutchouc servant à tenir les composants, ces rondelles doivent être jetées!



OUTILS REQUIS

- CLE A DOUILLE 2 x 13mm
- CLE DYNAMOMETRIQUE

NOTICE DE MONTAGE

- Placer la barre d'axe (article 1) dans le moyeu de roue arrière du coté droit.
- Placer l'entretoise du coté droit (article 2) dans le moyeu de roue arrière du coté droit. Ensuite, placer la protection crash (article 4), une rondelle M8 (article 5) et un écrou M8 (article 6). Ne pas serrer complètement l'écrou à ce stade.
- Placer l'entretoise du coté gauche (article 3) dans le moyeu de roue arrière du coté gauche. Ensuite, placer une protection crash (article 4), une rondelle M8 (article 5) et un écrou M8 (article 6).
- Serrer les 2 écrous en même temps à l'aide d'une clé anglaise et d'une douille 13mm de chaque coté, en veillant à ce que les écrous soient complètement engagés dans le filetage de la barre d'axe. Serrer à 20Nm. NE PAS TROP SERRER—LES ECROUS FIXENT L'ENSEMBLE.

ISSUE 1 10/10/2016 (HH)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P - at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

SP0074